



































	Rating (VA / W)	Runtime (minutes) ¹	Emerson Part Number	List Price GBP	Extended batteries	List Price GBP	Input Plug	Output Plugs	Comms Ports	Net/Tel protection	Intellistat SNMP WEB	Form factor (tower/rack)	Dimensions and weight (H x W x D - mm)	3rd year warranty (Code / List Price GBP)	APC SKU	Emerson Advantages
Liebert PSP Protection for Desktop Computers and Small Electronic Devices																
	500VA 300W	11 min	PSP500MT3-230U	67	-		C14/10A		USB	•	-	Tower	215 x 87 x 251 3.9 kg	PF1YR-MU-00 20	BE325-UK, BK350EI, BK500EI, BE400-UK, BH500INET	up to 50% more power; EPO; cold start; 2.4 kg less weight
	650VA 390W	8 min	PSP650MT3-230U	94	-		C14/10A		USB	•	-	Tower	215 x 87 x 251 3.9 kg	PF1YR-MU-01 27	BE550G-UK, BK650EI, BE700G-UK	up to 20% more power; EPO; cold start; 2.1 kg less weight
Liebert PSA Protection for Professional Workstations and Small Networking Equipment																
	500VA 300W	12	PSA500MT3-230U	107	-		C14/10A ²		USB	•	-	Tower	171x95x356 5.4 kg	PF1YR-MU-01 27	BR500I, SC420I	EPO; cold start; 1.1kg less weight
	650VA 390W	8.5	PSA650MT3-230U	128	-		C14/10A ²		USB	•	-	Tower	171x95x356 5.9 kg	PF1YR-MU-01 27	BR550GI, BR800I, SC620I	up to 20% more power; EPO; cold start; 0.6kg less weight
	1000VA 600W	12	PSA1000MT3-230U	206	-		C14/10A ²		USB	•	-	Tower	234x147x360 9.5 kg	PF1YR-MU-02 33	BR900GI, BR1000I, BR1200LDCI, SC1000I	up to 12% more power; EPO; cold start; 1.2kg less weight
	1500VA 900W	10.5	PSA1500MT3-230U	245	-		C14/10A ²		USB	•	-	Tower	234x147x360 11.6 kg	PF1YR-MU-04 67	BR1200GI, BR1500GI, BR1500I, BR1500LDCI, SC1500I	up to 25% more power; EPO; cold start; 1.1kg less weight
Liebert PSI Networking, Entry Level Server Protection																
	750VA 675W	11	PS750RT3-230	305	-		C14/10A ²		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 490.5 25 kg	PF1YR-MU-03 50	SMT750I, SMT750RM12U, SUA750I, SUA750RM11U/2U	35% more active power; PF 0.9; EPO; R/T; 2.2 kg less weight; (+4 outlets)
	1000VA 900W	12	PS1000RT3-230	329	-		C14/10A ²		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 490.5 28 kg	PF1YR-MU-03 50	SMT1000I, SMT1000RM12U, SUA1000I, SUA1000RM11U/2U	30% more active power; PF 0.9; EPO; R/T; 8kg less weight; (+4 outlets)
	1500VA 1350W	9	PS1500RT3-230	420	-		C14/10A ²		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 490.5 28 kg	PF1YR-MU-04 67	SMT1500I, SMT1500RM12U, SUA1500I, SUA1500RM12U	30% more active power; PF 0.9; EPO; R/T; 7.4kg less weight; (+4 outlets)
	2200VA 1980W	11	PS2200RT3-230	684	-		C20/16A ³		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 700.5 42 kg	PF1YR-MU-05 120	SMT2200I, SMT2200RM12U, SUA2200I, SUA2200RM12U	Rack/Tower; EPO; 8.3kg less weight
	3000VA 2700W	9	PS3000RT3-230	873	-		C20/16A ³		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 700.5 46 kg	PF1YR-MU-05 120	SMT3000I, SMT3000RM12U, SUA3000I, SUA3000RM12U	Rack/Tower; EPO; 6.3kg less weight
Liebert PSI-XR Networking, Entry Level Server Protection with Scalable Runtime																
	1000VA 900W	15 (+)	PS1000RT3-230XR	427	PSRT3-24VBXR	391	C14/10A ²		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 490.5 25 kg	PF1YR-MU-03 50	SMX750I, SMX1000I, SUA750XLI, SUA1000XLI	10% more active power; PF 0.9; EPO; Rack/Tower
	1500VA 1350W	13 (+)	PS1500RT3-230XR	505	PSRT3-24VBXR	391	C14/10A ²		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 490.5 28 kg	PF1YR-MU-04 67	SMX1500RM12U, SU1400RMXLIB3U, SUM1500RMXLI2U	10% more active power; PF 0.9; EPO; Rack/Tower
	2200VA 1980W	14 (+)	PS2200RT3-230XR	781	PSRT3-48VBXR	391	C20/16A ³		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 700.5 42 kg	PF1YR-MU-05 120	SMX2200RMHV2U, SUA2200XLI, SUA2200RMXLI3U	EPO, Rack/Tower
	3000VA 2700W	13 (+)	PS3000RT3-230XR	1145	PSRT3-48VBXR	391	C20/16A ³		USB	•	Optional (188) ⁴	Tower / Rack	2U 88 x 440 x 700.5 46 kg	PF1YR-MU-05 120	SMX3000RMHV2U, SUA3000RMXLI3U, SUA3000XLI, SUM3000RMXLI2U	EPO, Rack/Tower
Liebert GXT4 Networking and Server Power Protection																
	700VA 630W	27 (+)	GXT4-700RT230E (+K)	484	GXT4-48VBATTE (+K)	382	C14/10A ²		Serial/USB	-	Optional (188) ⁵	Tower / Rack	2U 85 x 408 x 430 18.2 kg	PF1YR-MU-03 50		No rating available here by APC.
	1000VA 900W	17 (+)	GXT4-1000RT230E (+K)	551	GXT4-48VBATTE (+K)	382	C14/10A ²		Serial/USB	-	Optional (188) ⁵	Tower / Rack	2U 85 x 408 x 430 18.2 kg	PF1YR-MU-03 50	SURT1000XLI, SURT1000RMXLI	28% less active power; PF 0.9; 4 dry-contacts not included; Rack/Tower; 4.8kg more weight
	1500VA 1350W	12 (+)	GXT4-1500RT230E (+K)	790	GXT4-48VBATTE (+K)	382	C14/10A ²		Serial/USB	-	Optional (188) ⁵	Tower / Rack	2U 85 x 497 x 430 23.2 kg	PF1YR-MU-05 120		No rating available here by APC.
	2000VA 1800W	12 (+)	GXT4-2000RT230E (+K)	977	GXT4-48VBATTE (+K)	382	C20/16A ³		Serial/USB	-	Optional (188) ⁵	Tower / Rack	2U 84 x 497 x 430 24.7 kg	PF1YR-MU-05 120	SRT2200XLI, SRT2200RMXLI	More depth (594 mm in APC); more acoustic noise (<55dBa); no parallel operation; no LIFE compatible EPO; Rack/Tower
	3000VA 2700W	12 (+)	GXT4-3000RT230E (+K)	1369	GXT4-72VBATTE (+K)	483	C20/16A ³		Serial/USB	-	Optional (188) ⁵	Tower / Rack	2U 85 x 602 x 430 31.9 kg	PF1YR-MU-06 212	SRT3000XLI, SRT3000RMXLI	In APC, more depth (632 mm); more acoustic noise (<55dBa); 4 dry-contacts signals not included; EPO; Rack/Tower; 22.5kg less weight
	5000VA 4000W	21 (+)	GXT4-5000RT230E (+K)	1856	GXT4-240VBATTE (+K)	882	Hardwired		USB	-	Optional (188) ⁵	Tower / Rack	5U 217 x 430 x 574 60 kg	Please contact us	SRT5KXLI, SRT5KRMXLI	No integrated & detachable POD; more depth (719 mm in APC); more acoustic noise (55dBa); no parallel operation; no LIFE compatible
	6000VA 4800W	17 (+)	GXT4-6000RT230E (+K)	2314	GXT4-240VBATTE (+K)	882	Hardwired		USB	-	Optional (188) ⁵	Tower / Rack	5U 217 x 430 x 574 60 kg	Please contact us	SRT6KXLI, SRT6KRMXLI	No integrated & detachable POD; more depth (719 mm in APC); more acoustic noise (55dBa); no parallel operation; no LIFE compatible
	10000VA 9000W	12 (+)	GXT4-10KRT230E (+K)	3553	GXT4-240VBATTE (+K)	882	Hardwired		USB	-	Optional (188) ⁵	Tower/Rack	6U 261 x 430 x 581 70 kg	Please contact us	SRT10KXLI, SRT10KRMXLI	No integrated & detachable POD; more depth (719 mm in APC); more acoustic noise (55dBa); no parallel operation; no LIFE compatible
	10000VA 9000W	12 (+)	GXT3-1000T230	3296	GXT3-240BATTCE	1637	Hardwired	Hardwire	USB	-	Optional (188) ⁵	Tower	800 x 300 x 675 105 kg	Please contact us	SRT10KXLI	No parallel operation in APC; less acoustic noise, no LIFE compatibility

(+) Scalable runtime with extension battery cabinets

(+K) Rackmount kit optional RMKIT18-32 E 108


For more runtime options please turn page

1) 50% charge, fully charged battery, at 20° C
2) For input cord, use input power cord of PC or order ref. 76789102 List price 39
3) Input cable included in box
4) SNMP/Web card: IS-WEBRT3, List 188
5) SNMP/Web card: IS-WEBCARD, List 188

• Available - Not Available



WARRANTY: 2 YEARS



Liebert PSA Professional Workstations Protection

Liebert PSA

	300VA	650VA	1000VA	1500VA
Load %	300W	390W	600W	900W
10%	173	133	151	148
25%	65	59	55	62
50%	28	21	22	23
75%	14	11	11	12
#####	7	5	5	5

Liebert PSI Networking, Entry Level Server Protection

Liebert PSI and PSI-XR with internal batteries

	1000VA	1500VA	2200VA	3000VA
Load %	900W	1350W	1980W	2700W
10%	82	81	76	75
25%	43	32	32	32
50%	15	13	14	13
75%	9	8	8	8
#####	6	5	5	5

Liebert PSI-XR Networking, Entry Level Server Protection with Scalable Runtime

internal + 1 battery cabinets					internal + 2 battery cabinets				internal + 3 battery cabinets				internal + 4 battery cabinets				internal + 5 battery cabinets				internal + 6 battery cabinets			
Load %	1000VA	1500VA	2200VA	3000VA	900W	1350W	1980W	2700W	900W	1350W	1980W	2700W	900W	1350W	1980W	2700W	900W	1350W	1980W	2700W	900W	1350W	1980W	2700W
10%	272	222	161	142	438	357	241	205	614	492	322	267	789	627	483	329	964	762	564	392	1140	897	644	454
25%	139	109	80	70	231	175	128	106	324	241	170	139	385	308	255	171	509	374	298	204	601	440	341	236
50%	73	55	45	31	129	95	67	56	181	131	95	73	233	167	143	95	285	203	167	113	336	239	191	131
75%	51	31	25	17	84	61	47	31	126	84	62	50	162	114	100	62	197	139	116	74	233	163	133	85
#####	31	18	15	12	65	46	29	18	96	64	48	31	124	82	72	47	151	106	84	56	179	124	102	65

Liebert GXT4 700-3000 RT Networking and Server Power Protection

internal batteries						internal + 1 battery cabinets					internal + 2 battery cabinets					internal + 3 battery cabinets					internal + 4 battery cabinets					internal + 5 battery cabinets					internal + 6 battery cabinets				
Load %	700VA	1000VA	1500VA	2000VA	3000VA	630W	900W	1350W	1800W	2700W	630W	900W	1350W	1800W	2700W	630W	900W	1350W	1800W	2700W	630W	900W	1350W	1800W	2700W	630W	900W	1350W	1800W	2700W	630W	900W	1350W	1800W	2700W
10%	105	91	75	81	91	427	334	321	222	302	480	457	404	426	431	480	480	432	451	455	480	480	480	466	480	480	480	480	480	480	480	480	480	480	480
20%	62	38	36	37	39	303	166	152	137	139	434	333	306	201	205	461	442	399	322	325	480	460	428	421	423	480	467	434	438	440	480	480	456	450	452
30%	37	31	23	23	23	164	138	108	94	95	329	224	175	149	150	439	337	284	195	196	458	436	320	306	307	465	447	410	331	332	480	458	434	420	421
40%	32	23	16	16	16	145	108	81	66	66	273	166	142	124	124	345	305	179	154	155	442	340	286	192	192	452	428	316	224	225	462	442	404	319	319
50%	27	17	12	12	12	126	92	66	49	48	203	151	123	97	97	323	208	155	136	136	425	315	201	157	157	438	341	286	189	189	451	426	314	217	217
60%	22	14	9	9	9	106	72	51	39	41	164	135	100	75	76	300	166	137	111	112	336	218	161	142	143	425	320	201	158	159	440	341	284	186	187
70%	18	11	7	7	7	94	56	40	34	34	153	113	81	61	63	213	155	126	96	98	319	195	149	127	128	344	227	161	146	147	428	323	201	159	160
80%	15	9	6	5	5	78	48	35	28	27	142	103	71	50	50	189	144	105	78	79	301	165	138	107	109	329	208	153	133	135	368	306	178	148	150
90%	13	8	5	4	4	69	40	31	23	23	131	92	62	41	45	163	132	94	68	70	213	156	126	95	97	315	189	144	120	122	336	217	155	137	139
#####	11	6	4	3	3	61	37	26	20	21	121	78	49	38	41	156	122	80	56	60	197	147	108	80	81	301	164	135	104	106	325	201	149	126	128

Liebert GXT4 5000-6000-10000 RT and Liebert GXT3 10000 T Networking and Server Power Protection

internal batteries			internal + 1 battery cabinets			internal + 2 battery cabinets			internal + 3 battery cabinets			internal + 4 battery cabinets			internal + 5 battery cabinets			internal + 6 battery cabinets			GXT3-10000T230				
Load %	5000VA	6000VA	10000VA	4000W	4800W	9000W	4000W	4800W	9000W	4000W	4800W	9000W	4000W	4800W	9000W	4000W	4800W	9000W	4000W	4800W	9000W	10000VA +1 cabinet+2 cabinet			
10%	105	97	98	211	194	165	427	341	311	441	429	344	480	463	436	480	464	449	480	480	459	10%	48	150	250
20%	52	47	42	140	122	99	220	185	144	326	303	166	428	338	213	436	422	312	457	445	330	20%	36	120	201
30%	40	33	25	102	83	53	154	140	99	204	167	133	312	227	153	339	318	166	428	339	202	30%	23	88	148
40%	27	22	17	76	62	42	130	108	68	160	146	99	209	166	127	304	208	144	327	304	157	40%	16	69	122
50%	21	17	12	53	48	31	105	91	49	143	126	74	164	150	99	203	165	123	285	206	138	50%	12	52	97
60%	17	14	9	48	42	25	91	72	42	126	105	53	151	134	77	166	153	100	207	165	120	60%	9	43	76
70%	14	11	7	43	35	20	74	53	35	107	92	48	138	113	64	155	140	80	167	154	100	70%	7	35	65
80%	12	9	6	38	28	17	64	49	28	97	76	42	124	103	51	145	127	69	158	143	81	80%	6	27	53
90%	10	8	5	32	25	14	51	45	25	81	66	42	108	92	47	134	110	53	149	133	72	90%	5	24	48
#####	9	6	4	27	22	12	48	41	21	73	53	31	100	78	42	123	101	49	140	122	63	#####	4	21	43

WARRANTY: 2 YEARS

Approximate runtimes in minutes at 25°C for batteries in new, unused condition.